

EndPoint Temperature RTD

Remotely monitoring your temperature RTD sensors



The EndPoint Temperature RTD is a ready-to-use LoRa radio emitter for transmitting temperature measurements. This product meets the needs to remotely supervise RTD sensor temperature measurement.

BENEFITS

- > Ready-to-use radio transmitter
- > LoRaWAN radio protocol
- > Range : up to 10km
- > Long-lasting autonomy
- > Waterproof
- > AES128 data encryption
- > Data history


APPLICATIONS

TO ALERT

Fault or fault detection : Detection of an abnormal temperature.

TO STRENGTHEN

Quality improvement : Monitor and monitor ambient parameters.



TECHNICAL SPECIFICATIONS

General informations

Frequency	LoRa 433 MHz / 868 MHz band
Protection level	IP67
Communication protocol	LoRaWAN V1.0.2. or proprietary radio

Performance

RF power	14 dBm (25 mW)
RF sensibility	Up to -140 dBm
Range (free rein)	Up to 10 km

Power Supply

Pile ER18505	3,6 V / 4 Ah
Autonomy	5 years, 1 message/Hour (SF12, BW125 @14 dBm)

Input

PT100 3 wires sensors

Temperature precision < 0.5°C from -40°C to +100°C. (with PT100 Classe A RTD)

Mechanical case

Size	80x80x60 mm
Weight	80g
Magnets attachment by option	



CONTACT

14, Place Marcel Dassault - BP 70048 - 31702 BLAGNAC CEDEX (France)

Tel. : +33(0) 5 34 36 10 00 | E-mail : sales-team@arcys.fr